

# CATALYTIC ALLOY FOR THE DISSOCIATION OF WATER INTO HYDROGEN AND OXYGEN AND METHOD OF MAKING

This application claims benefit of the filing date of U.S. Provisional Serial No. 60/212,261, filed June 19, 2000, the entire contents of which are hereby incorporated by reference.

## BACKGROUND OF THE INVENTION

### 1. Field of Invention.

This invention relates to an amalgam-free catalytic alloy of materials for the dissociation of water into hydrogen and oxygen gases, and to methods for making this alloy.

### 2. Description of Prior Art.

In the continuing effort to provide an alternative fuel to reduce dependence on fossil fuels and to reduce or eliminate the pollution from the burning of fossil fuels it is generally agreed that the element hydrogen is the most abundant fuel in the universe and the most non-polluting, since the reaction product of its combustion is pure water. Despite its widespread availability and obvious virtues, hydrogen has not yet been utilized as a fuel of choice due to a number of technological problems which have not as yet been solved. These problems generally relate to devising safe, efficient, and economical methods of production, storage, transport, and utilization of hydrogen in sufficient quantities to make use of this fuel economically feasible.

Many methods have been described for the generation of hydrogen gas in almost unlimited quantities. The elementary electrolysis of water, gasification of coal, steam reforming of natural gas, partial oxidation of heavy oils and the use of nuclear reactors to break down steam into its component elements are the most common. Without exception,

however, these schemes for production of large quantities of hydrogen gas require extensive capital equipment, large production capabilities, and an input of significant external energy.

In addition, hydrogen gas is a highly explosive element. Therefore the storage and transport of the gas as a fuel presents multiple problems in efficiency and safety which, despite numerous ingenious endeavors, have not as yet been solved sufficiently to provide a safe and economically viable utilization of the gas as an alternative fuel. To overcome the problems of storage and transport of the gas a number of investigators have devised various methods of generating the gas on a demand basis at the point of utilization. Though most utilize a thermo-chemical or electrochemical scheme to dissociate water into either hydrogen and a salt, or into hydrogen and oxygen, work has also been done on the reforming of natural gases and gasoline into hydrogen, carbon dioxide and carbon monoxide.

It is known that the alkali metals react with water to form hydrogen and the stable alkali metal hydroxide (see, e.g., U.S. Patents 5,817,157, 5,782,464, Checketts, the entire contents of which are hereby incorporated by reference). The foregoing reaction, however, is rapid and violent, the heat generated is intense, and explosion of the hydrogen often occurs. In order for the technique in the Checketts patent, for example, to provide sufficient hydrogen for any practical purpose the size of the sodium pellets presented sequentially to the water would have to be of such size as to initiate the violent, rapid and dangerous reaction noted.

It is also known that the reaction of alkali hydroxides with a metal and water will also release hydrogen and form the alkali-metal hydroxide (see, e.g., U.S. Patent 5,690,902, the entire contents of which is hereby incorporated by reference). These techniques, however, can also result in rapid and violent reaction. They also produce an alkali-metal hydroxide, which can rapidly deteriorate the efficacy of the technique. Numerous closed cycle, often multi-stepped processes, which dissociate water into hydrogen and oxygen are disclosed in U.S. Patents 3,821,358; 3,928,549; 4,011,305; 3,969,495 and 3,574,561, the entire contents of each of which is hereby incorporated by reference. Of particular interest are the simple

methods of dissociating water into hydrogen and oxygen as demonstrated in U.S. Patents 4,182,748; 4,207,095; 4,287,169, and 4,289,744, issued to Eugene R. Anderson, the entire contents of each of which are hereby incorporated by reference. These patents utilize a combination of alkali metals with an extender and catalysts to control the rate of reaction and to restore the alkali metals to their elemental state as the process proceeds.

Unfortunately, from the description of the invention in these related (Anderson) patents a person reasonably skilled in the art is unable, by following the procedures as described, to actually fabricate such a catalytic alloy that will function as claimed. The description describes a multi-step process in which an amalgam of mercury, aluminum and sodium is prepared; an alloy of metal extender and various catalysts are prepared; both the amalgam and alloy are ground to a fine powder; the powders are intermixed; and the mixture, under high pressure, is heated to the melting point of the mixture. The resulting product is then cooled and supposedly ready for use. While an amalgam of mercury, aluminum and sodium is a logical step to gain a mixture of two metals which will not naturally alloy, the procedures described for the formation of the amalgam at elevated temperatures in a graphite crucible in a nitrogen atmosphere will quite often result in the formation of fulminate of mercury, a highly explosive compound. While the amalgam is ostensibly a part of the finished product, the heating of the eutectic mass under pressure to its melting point requires a temperature considerably above the sublimation and boiling point of mercury. The result is that the mercury is driven off in a vapor, destroying the amalgam, and in a nitrogen atmosphere, also can form fulminate of mercury. At the elevated temperatures this compound can explode violently. (The Wills Point, Texas, "Chronicle" reported several such explosions in Mr. Anderson's facility in that community in 1979 and 1980). Additionally, as no provisions are made for the collection of the mercury fumes, which are highly poisonous, the atmosphere of the fabricating facility would be exceedingly hazardous to the operators.

In other words, though the patent claims a combination of an amalgam of mercury, sodium and aluminum with a catalytic alloy, no such combination can exist following the

described procedure. The amalgam would be destroyed, thus allowing the sodium and aluminum to separate; the homogenous mixing of the elements with the catalysts could not occur; thus the purpose of the invention is defeated.

In order for the chemical reactions to occur as described, it is necessary that water be brought into intimate contact with the sodium, that the formed sodium hydroxide be brought into intimate contact with the aluminum, and that the formed sodium-aluminum hydroxide be brought into intimate contact with the catalyst. By forming the alloy into a block in which the sodium and aluminum have been separated (no longer existing as an amalgam), and in which the major portion of the constituents are in the interior of the block, the contact of the water is limited to the surface of the block and the major portion of the alloy is therefore inert. It is interesting to note, as reported in "Texas Monthly", that in the decades following the issuance of the patents Mr. Anderson was unable to actually fabricate and use his invention.

## SUMMARY OF THE INVENTION

The present invention provides a method for combining sodium and aluminum into a single, substantially homogeneous alloy without the need to use potentially dangerous, toxic mercury compounds. The present invention also provides a catalytic alloy that is capable of dissociating water into hydrogen and oxygen, thereby allowing the hydrogen to be utilized as fuel.

In one embodiment, the invention relates to a substantially homogeneous catalytic alloy, containing aluminum, sodium, and lead. The lead allows the aluminum and the sodium to be combined together in a homogeneous solid solution without the need to form amalgams using mercury. In addition to the sodium, aluminum, and lead, the catalytic alloy can also contain other elements, such as platinum, copper, antimony, chromium, or combinations of one or more, or all, of these.

In another embodiment, the invention relates to a hydrogen production system, containing a reaction vessel having disposed therein the catalytic alloy described above, at least one inlet conduit adapted to conduct water to the reaction vessel, and at least one outlet conduit adapted to conduct hydrogen from the reaction vessel.

In another embodiment, the invention relates to a method of producing a substantially homogeneous alloy of aluminum and sodium by:

combining metallic materials comprising aluminum, sodium, and lead in an inert atmosphere;

heating the resulting mixture to a temperature of at least around 600 °C;



maintaining the temperature of this mixture above this minimum until the mixture is substantially molten; and

cooling the resulting molten mixture to form a substantially homogeneous alloy.

The invention will be more clearly understood by reference to certain of its specific embodiments, described in more detail below, which are not intended to limit the scope of the appended claims or of equivalents thereto.

#### DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

Without wishing to be bound by any theory, it is believed that the reactions of a catalytic alloy containing sodium and aluminum with water can be summarized as follows:



In addition, it is believed that the presence of other catalytic species in the alloy, such as platinum, copper, antimony, chromium, or combinations of these, can dissociate the  $\text{Na}_3\text{Al}(\text{OH})_6$  complex according to the reaction:



It can be computed from the foregoing that the stoichiometric ratio of aluminum to sodium to insure complete reaction is 1:5.13.

In general, it is desirable for the sodium present in the alloy to be in metallic form, and to be present in an amount ranging from about 0.1 parts by weight (pbw) to about 10 pbw, more particularly about 5 pbw, based on 1 pbw aluminum. It is desirable that lead be present as metallic lead in amounts ranging from about 0.1 pbw to about 10 pbw, more particularly about 7 pbw, based on 1 pbw aluminum. If present, it is desirable that platinum be in the form of metallic platinum or platinum black, in amounts ranging from about 0.01 pbw to about 0.1 pbw, more particularly about 0.04 pbw platinum, based on 1 pbw aluminum. If present, it is desirable that copper be present as metallic copper in amounts ranging from about 10 pbw to about 20 pbw, more particularly about 15 pbw copper, based on 1 pbw aluminum. If present, it is desirable that antimony be present as metallic antimony in amounts ranging from about 0.5 pbw to about 2.0 pbw, more particularly about 1.3 pbw antimony per pbw aluminum. If present, it is desirable that chromium be present in metallic form and in amounts ranging from about 0.1 pbw to about 1.0 pbw, more particularly about 0.5 pbw, per pbw aluminum.

In order for the catalytic alloy to function properly it is necessary that the stoichiometric quantities of aluminum and sodium be homogeneously distributed throughout the resulting alloy on an almost molecular level. In embodiments containing additional catalytic species, these elements should be in intimate contact with the additional species. Irrespective of whether the additional catalytic species are present, it is desirable that aluminum and sodium be exposed to the water to be dissociated. To produce a catalyst that accomplishes these objectives the following procedure has been devised. The description in Example 2 relates to a catalytic alloy having sodium, aluminum, lead, platinum, copper, antimony, and chromium. A similar procedure can be used to prepare other catalytic alloys

wherein one or more of these components have been omitted (except for sodium, aluminum, and lead) or wherein other components have been added.

#### EXAMPLE 1

A containment chamber was evacuated with a vacuum pump, and then flooded with argon gas to create an inert atmosphere. One (1) gram of aluminum pellets, 0.85 g sodium metal, and 0.60 g lead shot were placed into a crucible in the inert atmosphere and heated to about 600 °C. The metals were thoroughly mixed, and the temperature of the mixture raised to about 900 °C. The molten mixture was then poured into a conical mold and cooled to form an alloy button.

The alloy button was placed into a filtering flask containing 100 ml of distilled water, and the flask securely sealed with a rubber stopper. Upon contact with the water, hydrogen was evolved, and collected in a water-filled gas trap. The collected hydrogen was conducted to a nozzle, where it burned with a colorless flame.

#### EXAMPLE 2

The entire fabrication process should take place in an inert, desiccated atmosphere. This can be accomplished by replacing the air in an enclosed sealed chamber with either argon or helium, and circulating the inert gas constantly through a desiccant. A mixture of one part by weight aluminum powder, 5.13 parts by weight of sodium particles, and 0.04 parts by weight of platinum black powder is placed into a carbide crucible and thoroughly mixed. To this mixture is added 7 parts by weight of powdered lead. The crucible is placed into an electric furnace and the mixture heated to 600°C. Once the temperature is achieved it is maintained and the following ingredients are added sequentially. Copper powder, 15 parts by weight; antimony powder, 1.3 parts by weight; chromium powder, 0.5 parts by weight. The mixture is then heated to 1500°C until the entire mass is liquid. While at this temperature the liquid alloy is slowly poured on to an oscillating ceramic paddle which breaks the stream into small droplets. These droplets are allowed to fall into a refrigerated

stainless steel tube where they coalesce into a porous mass of solid particles. The mass is allowed to cool to ambient temperature, is removed from the stainless steel tube and placed into an air tight plastic bag. The finished alloy may then be taken from the inert, desiccated atmosphere, and is ready for utilization.

It is understood that all of the various combinations of ingredients as described in the Anderson patents may be fabricated in this manner, provided that first the aluminum and sodium (and optionally platinum) are alloyed with lead, and then the additional catalysts and extenders are added sequentially and then heated to a liquid temperature. The formation and solidification of the alloy into small droplets to form a porous mass is essential to maximizing contact between the active, catalytic species in the alloy and water molecules in the dissociation of water. The larger surface area and intimate contact by water with the various ingredients of the alloy will allow the accomplishment of the goal desired, but not realized, by the Anderson patents.

In use the porous mass of catalytic alloy can be placed into a cylindrical metal tube fitted at one end with a connection for the input of water and at the other with an outlet for the generated gases. The rate of reaction, thus the quantity of gases formed, will be in direct proportion to the quantity of water injected into the apparatus. The reaction begins simultaneously with the input of water and ceases when the water flow is turned off.

As the gases are generated in stoichiometric proportions there is sufficient oxygen present to completely combust the generated hydrogen without the necessity of additional air or oxygen. The gases can therefore be ignited and combusted in a closed system. In a conventional internal combustion engine system the surplus gas contained in the inspired air necessary for compression to achieve useable power could be replaced by injected water vapor. This would provide the necessary expansion of gases and water vapor to provide useable power and simultaneously eliminate all noxious emissions, replacing the COX and NOX emissions with pure water vapor. The water vapor could be condensed and re-used in



	1970	1980	1990	2000	2010	2020	2030	2040	2050	2060	2070	2080	2090	2100	2110	2120	2130	2140	2150	2160	2170	2180	2190	2200	2210	2220	2230	2240	2250	2260	2270	2280	2290	2300	2310	2320	2330	2340	2350	2360	2370	2380	2390	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500	2510	2520	2530	2540	2550	2560	2570	2580	2590	2600	2610	2620	2630	2640	2650	2660	2670	2680	2690	2700	2710	2720	2730	2740	2750	2760	2770	2780	2790	2800	2810	2820	2830	2840	2850	2860	2870	2880	2890	2900	2910	2920	2930	2940	2950	2960	2970	2980	2990	3000	3010	3020	3030	3040	3050	3060	3070	3080	3090	3100	3110	3120	3130	3140	3150	3160	3170	3180	3190	3200	3210	3220	3230	3240	3250	3260	3270	3280	3290	3300	3310	3320	3330	3340	3350	3360	3370	3380	3390	3400	3410	3420	3430	3440	3450	3460	3470	3480	3490	3500	3510	3520	3530	3540	3550	3560	3570	3580	3590	3600	3610	3620	3630	3640	3650	3660	3670	3680	3690	3700	3710	3720	3730	3740	3750	3760	3770	3780	3790	3800	3810	3820	3830	3840	3850	3860	3870	3880	3890	3900	3910	3920	3930	3940	3950	3960	3970	3980	3990	4000	4010	4020	4030	4040	4050	4060	4070	4080	4090	4100	4110	4120	4130	4140	4150	4160	4170	4180	4190	4200	4210	4220	4230	4240	4250	4260	4270	4280	4290	4300	4310	4320	4330	4340	4350	4360	4370	4380	4390	4400	4410	4420	4430	4440	4450	4460	4470	4480	4490	4500	4510	4520	4530	4540	4550	4560	4570	4580	4590	4600	4610	4620	4630	4640	4650	4660	4670	4680	4690	4700	4710	4720	4730	4740	4750	4760	4770	4780	4790	4800	4810	4820	4830	4840	4850	4860	4870	4880	4890	4900	4910	4920	4930	4940	4950	4960	4970	4980	4990	5000	5010	5020	5030	5040	5050	5060	5070	5080	5090	5100	5110	5120	5130	5140	5150	5160	5170	5180	5190	5200	5210	5220	5230	5240	5250	5260	5270	5280	5290	5300	5310	5320	5330	5340	5350	5360	5370	5380	5390	5400	5410	5420	5430	5440	5450	5460	5470	5480	5490	5500	5510	5520	5530	5540	5550	5560	5570	5580	5590	5600	5610	5620	5630	5640	5650	5660	5670	5680	5690	5700	5710	5720	5730	5740	5750	5760	5770	5780	5790	5800	5810	5820	5830	5840	5850	5860	5870	5880	5890	5900	5910	5920	5930	5940	5950	5960	5970	5980	5990	6000	6010	6020	6030	6040	6050	6060	6070	6080	6090	6100	6110	6120	6130	6140	6150	6160	6170	6180	6190	6200	6210	6220	6230	6240	6250	6260	6270	6280	6290	6300	6310	6320	6330	6340	6350	6360	6370	6380	6390	6400	6410	6420	6430	6440	6450	6460	6470	6480	6490	6
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

[illegible]